

# QSFP-850-MMF

SFP Optical Modul



- Multiple mode double fiber.
- MPO port.
- 850 nm sending, and 850 nm receiving.
- Transmission distance up to 100 meters by OM3 and 150 meters by OM4.

## Series Overview

Industrial Optical Module Series is a hot-pluggable device with a unique high integration design. Developed to adapt to even the harshest of environments, it has a wide operating temperature range and is Plug and play (PnP) .

## Scene

This Series is widely used in various broadband data transmission scenarios, such as in intelligent traffic, telecom, security, finance, custom, shipping, electricity, water conservancy and oil fields. It is also suitable for work with switches and other devices.

## Technical Specification

### Hardware

Optical Fiber Type	Multiple mode double fiber
Optical Port Type	MPO
Speed	40 Gbps

### Performance

Wavelength	850 nm
Transmission Distance	100 m (328.08 ft)
Storage Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Operating Humidity	0%–85% (RH), non-condensing
Operating Temperature	0 °C to +55 °C (32 °F to +131 °F)
Storage Humidity	0%–85% (RH), non-condensing
Product Dimensions	127 mm × 18.3 mm × 8.3 mm (5.00" × 0.72" × 0.33")

## Ordering Information

Type	Model	Description
Accessories	GSFP-1310-20-SMF	Speed 1Gbps Single mode double fiber; 1310 nm sending, and 1310 nm receiving; Transmission distance up to 20 km
	GSFP-1310R-20-SMF	Speed 1Gbps Single mode single fiber; 1550 nm sending, and 1310 nm receiving; Transmission distance up to 20 km
	GSFP-1310T-20-SMF	Speed 1Gbps Single mode single fiber; 1310 nm sending, and 1550 nm receiving; Transmission distance up to 20 km
	SFP-1310T-20-SMF	Speed 100Mbps Single mode single fiber; 1310 nm sending, and 1550 nm receiving; Transmission distance up to 20 km
	SFP-1310R-20-SMF	Speed 100Mbps Single mode single fiber; 1550 nm sending, and 1310 nm receiving; Transmission distance up to 20 km
	TSFP-850-MMF	Speed 10Gbps Multiple mode double fiber; 850 nm sending, and 850 nm receiving; Transmission distance up to 300 m
	GSFP-850-MMF	Speed 1Gbps Multiple mode double fiber; 850 nm sending, and 850 nm receiving; Transmission distance up to 550 m
	SFP-850-MMF	Speed 100Mbps Multiple mode double fiber; 850 nm sending, and 850 nm receiving; Transmission distance up to 2 km
	TSFP-1270T-20-SMF	Speed 10Gbps Single mode single fiber; 1270 nm sending, and 1330 nm receiving; Transmission distance up to 20 km
	TSFP-1270R-20-SMF	Speed 10Gbps Single mode single fiber; 1330 nm sending, and 1270 nm receiving; Transmission distance up to 20 km

## Dimensions (mm[inch])

